

# PB-Li 12-200



# POWER BOOZ®

high power **battery series**

**LFP** LiFePO<sub>4</sub> LITHIUM BATTERY



## ELECTRICAL SPECIFICATIONS

Nominal Voltage	12,8 V
Nominal Capacity	200 Ah
Open Circuit Volt. @ 100%	13,6 V
Energy	2560 Wh
Internal Resistance	≤ 50 mΩ
Self Discharge	< 3 % / month

## DISCHARGING

Max. cont. Discharge Current	200 A
Peak Discharge Current	300 A (<30s)
BMS Discharge Cut-Off	350 A
Rec. Low Voltage Cut-Off	11 V
BMS Cut-Off	10,4 V
Reconnect Voltage	11,2 V

## TEMPERATURES

Discharge Temperature	-20 bis +60°C
Charge Temperature	0 bis +60 °C
Storage Temperature	0 bis +60 °C

## COMMUNICATION

Bluetooth 4.0 with App Android/iOS

## MECHANICAL SPECIFICATIONS

Dimensions (LxWxH)	353 x 350 x 188 mm
Weight	25,3 kg
Terminal Type	M8
Case Material	Metal
Enclosure Protection	IP 56
Cell Type / Chemistry	Prismatic LiFePO <sub>4</sub>

## CHARGING

Recomm. Charge Current	50 A
Recomm. Charge Voltage	14,4 V - 14,6 V
BMS Voltage Cut-Off	14,6 V

## COMPLIANCE

Certificates	CE UN38.3 UL1642 & IEC2133
Shipping Classification	UN 3480, Klasse 9



A. Müller GmbH  
Tholeyer Straße 32  
D-66620 Nonnweiler-Primstal  
Mail: info@batterien-mueller.de

